




NEXTORCH

ENGLISH



P5G

Learn more on
www.nextorch.com

SPECIFICATIONS

ANSI / PLATO-FL1	Momentary on (white / green)	High (white / green)	Low (white / green)	Strobe (white / green)	Hidden S.O.S.
Light Output	800 lm / 200 lm	800 lm / 200 lm	45 lm / 27 lm	800 lm / 200 lm	100 lm / 45 lm
Run Time	—	3 h 45 min / 5 h	27 h / 30 h	—	—
Beam Distance	246 m / 224m				
Impact Resistance	1 m				
Waterproof	IPX4				
Weight and Dimensions	Weight: 185 g / 6.53 oz (Without Battery) Size: 168 mm (Length) × 40 mm (Head Diameter) × 26 mm (Body Diameter)				
Body Material	Light Source: CREE XP-LV5 LED / CREE XP-E2 GREEN LED Aerospace grade aluminum 6061-T6				


Above tested specifications are strictly based on the standard of ANSI / PLATO-FL1. We tested P5G with 1 × 18650 (2600mAh) Lithium battery in 22°C ± 3°C. The specifications might be different when using a different battery or testing in a different environment.

FEATURES


- Dual-Light technology, white light/green light combination
- Micro USB direct charging design
- White light max output at 800 lumens, green light max output at 200 lumens
- DUO Switch operates in 2modes, plus tactical strobe and S.O.S.
- Powered by one 18650 Li-ion battery or two CR123A batteries

INSTRUCTIONS


- Battery Installation




- ON / OFF Momentary ON / OFF




- Constant ON / OFF




- Mode Switch



- Double - Click Strobe



- Light Source Selection



HOW TO CHARGE

1. Pull the tail ring up to reveal the charging USB interface.
2. Connect the flashlight and computer via a USB cable.
3. When the light indicator appears:
 - 1) Red: charging in progress.
 - 2) Green: fully charged.
 - 3) Charging time about 4 hours.



MAINTENANCE

1. Being infected with seawater or any corrosive chemicals, please rinse immediately with clean water.
2. Please use high quality batteries; Remove batteries when not working for a long time, and then store in a cool dry place.
3. If the waterproof O-ring is damaged, replace it immediately.

WARRANTY

1. NEXTORCH offers 5-year warranty.
2. NEXTORCH warrants our products to be free from any defects in workmanship and material, we will replace or return faulty item. NEXTORCH reserves the right to replace similar products if original one is discontinued.
3. The warranty excludes other accessories, but rechargeable batteries are warranted for 1 year from date of purchase.
4. Any accessories or products are not covered in the warranty, NEXTORCH can repair for users with reasonable fee.
5. Please scan the below QR code and access to NEXTORCH website (www.nextorch.com) to register your purchasing. Email us info@nextorch.com Call us: 0086-662-6602777 Or contact local dealer




CONTACT WITH NEXTORCH DESIGNER

In order to improve NEXTORCH, we appreciate you could offer our designers your after-use feedback and creative suggestions by scanning the following QR code. Thank you!



NEXTORCH

中文



P5G

请登录: www.nextorch.com
获取更详尽的产品资讯。

性能参数

ANSI/PLATO-FL1	点射(白/绿)	高亮(白/绿)	低亮(白/绿)	爆闪(白/绿)	S.O.S.
亮度	800流明/200流明	800流明/200流明	45流明/27流明	800流明/200流明	100流明/45流明
续航时间	—	3小时45分钟/5小时	27小时/30小时	—	—
照射距离	246米/224米				
防跌高度	1米				
防水等级	IPX4				
规格	重量: 185克(不含电池) 尺寸: 168毫米(长) × 40毫米(头径) × 26毫米(筒径)				
材料	光源: CREE XP-LV5 LED / CREE XP-E2 GREEN LED 筒身: 航天等级强化铝材6061-T6, III型硬质阳极氧化表面处理				


上述参数严格按照ANSI/PLATO FL1 标准测试所得, 测试电池为1节18650 (2600mAh) 锂离子电池, 测试温度22°C ± 3°C, 测试电池或环境不同, 性能参数可能会有差异。

产品特点


- 双光源设计, 单反光杯实现800流明白光, 200流明绿光双高亮输出
- 专利双光源结构, 单手操作, 方便快捷
- 尾部Micro USB直接充电设计, LED充电显示
- DUO功能开关设计, 单开关实现战术点射及轻触模式切换
- 兼容1节18650及2节CR123A电池

快速入门


- 电池安装



- 打开/关闭 瞬时点亮




- 常亮




- 模式切换



- 双击爆闪



- 选择光源



如何充电

1. 上拉尾部卡环并转动一定角度, 插入数据线, 连接电源, 即可实现多样化方式充电(当使用1 × 18650可充电锂离子电池时)当充电箱指示灯显示:
 - 1) 红色: 充电进行中
 - 2) 绿色: 充电完毕
 - 3) 充电时间: 约4小时



保养注意事项

1. 当沾到海水或腐蚀性物品时, 请及时用清水清洗;
2. 请使用优质电池, 并且在长时间不使用时, 请将电池取出, 放在阴凉处保存; 若产品采用不可拆卸的内置电池, 切勿自行更换电池, 以免导致产品无法正常运行或电池损坏。
3. 长时间使用后若发现O型圈磨损, 请及时更换。

售后/保修条款

1. 15天保换: NEXTORCH产品自售出日起15天内, 在正常使用的情况下, 若出现质量问题, 可免费更换同型号产品; 若该产品已停止生产, 则调换该型号升级版或不低于原产品性能的其他产品;
2. 5年免费保修期: NEXTORCH产品自售出日起5年内, 在正常使用的情况下, 若出现质量问题, 享受免费维修服务;
3. 充电电池类产品保修期为1年, 产品附加配件不在保修范围内;
4. 终身有限保修: 因不当使用引起的产品损坏或超出免费保修时间的产品, 我司将提供有偿保修, 费用以实际更换材料费用为准, 不另收取人工费用;
5. 我司提供多种渠道进行维修服务, 您可以通过扫描如下二维码在官网进行登记、发邮件至service@nextorch.com、致电400-8300-799或直接联系当地经销商进行售后服务;



与纳丽德设计师沟通

为更好地改进我们的产品, 您如果有产品改进反馈或创意提供给我们的设计师, 请扫描下方二维码, 联系我们的产品设计师。



成品尺寸: 80mm × 40mm
 展开尺寸: 320mm × 80mm
 检验标准: 尺寸 ± 1mm
 材质: 80克双胶纸
 颜色: K
 要求: 双面印刷, 虚线折痕, 按标注正面。